

PXM



JET PX 203E



JET PX 404E

Application Limits

- Suction head up to 7m
- Liquid temperature up to +40°C
- Ambient temperature up to +40°C
- Max. Working pressure: 4.8bar
- Voltage fluctuation should not exceed 10% of rated value.
- pH: 6.5 to 8.5

Advantages & Features

- Suitable for transferring water without abrasive particles or other liquid whose properties are similar to water.
- Widely used in garden irrigation, vegetable greenhouse water supply, breeding industry water supply and drainage, various corollary equipment, etc.

Performance Data

Model		Power		Max. Flow (m ³ /h)	Max. Head (m)	Head Range (m)	Max. Suction (m)	Packing Dim. L x W x H(mm)	G.W (kg)	20'Loading Qty. (pcs)
Single-Phase	Three-Phase	kW	HP							
PXm203	PX203	0.46	0.6	5	32	4 ~ 32	7	460 × 225 × 255	10.5	1195
PXm204	PX204	0.55	0.75	5.4	44	4 ~ 44	7	460 × 225 × 255	11	1195
PXm402	PX402	0.46	0.6	8	22	4 ~ 22	7	460 × 225 × 255	10.5	1195
PXm403	PX403	0.55	0.6	8.4	33.5	4 ~ 33.5	7	460 × 225 × 255	11	1195
PXm404	PX404	0.75	1	9	45	4 ~ 45	7	460 × 225 × 255	11.5	1195
PX203E	-	0.37	0.5	5	32	10 ~ 30	7	367 × 165 × 289	9.5	459
PX404E	-	0.75	1	9	45	10~40	7	450 × 235 × 530	15.3	430
PX804E	-	1.47	2.0	14	45	10 ~ 40	7	447 × 200 × 534	20.7	1151