

Performance Data

Model	Power		Q (m ³ /h)	Head Range (m)							Packing Dim. (L×W×H) mm	G.W.(kg)		
	kW	HP		8	10	12	14	16	18	20		50.7	59.5	
BL(T)16-2	2.2	3	H (m)	27	26	25	24	22	21	19	19~27			775x325x400
BL(T)16-3	3	4		41	40	38	37	34	32	29	29~41	885x325x415	59.6	68.6
BL(T)16-4	4	5.5		54	53	52	49	46	43	38	38~54	945x325x415	68.8	77.8
BL(T)16-5	5.5	7.5		68	67	65	62	58	54	48	48~68	1115x400x490	89.8	98.6
BL(T)16-6	5.5	7.5		82	80	78	74	70	64	58	58~82	1175x400x490	91.7	100.6
BL(T)16-7	7.5	10		96	95	91	87	82	76	68	68~96	1210x400x490	95.9	106.8
BL(T)16-8	7.5	10		110	108	104	99	94	86	77	77~110	1265x400x490	97.3	108.6
BL(T)16-10	11	15		138	136	131	125	118	109	97	97~138	1425x520x560	178	186.8
BL(T)16-12	11	15		166	162	157	150	141	130	116	116~166	1515x520x560	181.8	190.6
BL(T)16-14	15	20		194	190	184	175	166	152	136	136~194	1605x520x560	196.5	204.3
BL(T)16-16	15	20		222	217	210	200	189	174	156	156~222	1695x520x560	200.3	208.2

Model	Power		Q (m ³ /h)	Head Range (m)							Packing Dim. (L×W×H) mm	G.W.(kg)		
	kW	HP		14	16	18	20	22	24	26		174.4	183.3	
BL(T)20-2	2.2	3	H (m)	27	25	24	23	22	20	18	18~27			775x325x400
BL(T)20-3	4	5.5		40	38	37	35	33	30	27	27~40	945x325x415	68.9	75.9
BL(T)20-4	5.5	7.5		54	51	49	47	44	41	37	37~54	1115x400x490	87.7	95.5
BL(T)20-5	5.5	7.5		67	62	60	58	55	50	45	45~67	1115x400x490	91	98.8
BL(T)20-6	7.5	10		81	75	73	70	66	61	55	55~81	1175x400x490	95	104.8
BL(T)20-7	7.5	10		95	89	86	82	77	71	65	65~95	1210x400x490	97.3	107.4
BL(T)20-8	11	15		109	102	99	94	89	82	75	75~109	1335x520x560	174.4	183.3
BL(T)20-10	11	15		136	128	124	118	111	103	95	95~136	1425x520x560	179.4	188.3
BL(T)20-12	15	20		164	154	149	142	133	124	114	114~164	1515x520x560	194.3	202.4
BL(T)20-14	15	20		192	180	174	166	156	145	133	133~192	1605x520x560	198.1	206.4
BL(T)20-17	18.5	25	234	219	212	202	190	177	162	162~234	1805x520x560	220.6	231	

Performance Data

Model	Power		Q (m ³ /h)	Head Range (m)							Packing Dim. (L×W×H) mm	G.W.(kg)	
	kW	HP		16	20	24	28	32	36	1915x485x562 <th rowspan="2">230.4 <th rowspan="2">233.2 </th></th>		230.4 <th rowspan="2">233.2 </th>	233.2
BL(T)32-2-2	3	4	H (m)	29	28	26	23	20	16		16~29		
BL(T)32-2	4	5.5		36	34	32	29	27	23	23~36	1315x425x512	96.5	98.1
BL(T)32-3-2	5.5	7.5		47	44	41	38	33	28	28~47	1315x425x512	115.9	117.2
BL(T)32-3	5.5	7.5		54	51	48	44	40	35	35~54	1315x425x512	115.9	117.2
BL(T)32-4-2	7.5	10		65	62	58	53	46	40	40~65	1315x425x512	121.9	123.1
BL(T)32-4	7.5	10		72	69	65	59	53	47	47~72	1315x425x512	121.9	123.1
BL(T)32-5-2	11	15		83	79	74	68	60	52	52~83	1655x485x562	204.2	208.4
BL(T)32-5	11	15		90	86	81	74	67	59	59~90	1655x485x562	204.2	208.4
BL(T)32-6-2	11	15		101	97	90	83	74	65	65~101	1655x485x562	208.2	212.3
BL(T)32-6	11	15		108	104	97	90	81	72	72~108	1655x485x562	208.2	212.3
BL(T)32-7-2	15	20		119	114	107	98	88	78	78~119	1655x485x562	222.3	226.2
BL(T)32-7	15	20		126	121	113	105	95	85	85~126	1655x485x562	222.3	226.2
BL(T)32-8-2	15	20		136	131	123	114	102	90	90~136	1915x485x562	230.4	233.2
BL(T)32-8	15	20		144	138	130	120	109	97	97~144	1915x485x562	230.4	233.2
BL(T)32-9-2	18.5	25		154	148	140	129	117	102	102~154	1915x485x562	251.4	254
BL(T)32-9	18.5	25		162	156	147	136	124	109	109~162	1915x485x562	251.4	254
BL(T)32-10-2	18.5	25		175	166	157	146	131	115	115~175	1915x485x562	255.4	257.9
BL(T)32-10	18.5	25		182	173	164	152	138	122	122~182	1915x485x562	255.4	257.9
BL(T)32-11-2	22	30		193	184	173	164	146	128	128~193	2065x545x612	305.1	306.5
BL(T)32-11	22	30		200	191	180	168	153	135	135~200	2065x545x612	305.1	306.5
BL(T)32-12-2	22	30		211	201	189	178	160	140	140~211	2065x545x612	308.9	310.3
BL(T)32-12	22	30		218	208	196	184	167	147	147~218	2065x545x612	308.9	310.3
BL(T)32-13-2	30	40		230	218	206	193	174	153	153~230	2365x595x662	390.2	390.5
BL(T)32-13	30	40		237	225	213	200	181	160	160~237	2365x595x662	390.2	390.5
BL(T)32-14-2	30	40		247	235	222	210	189	165	165~247	2365x595x662	394.2	394.4
BL(T)32-14	30	40		255	242	229	216	196	172	172~255	2365x595x662	394.2	394.4
BL(T)32-15-2	30	40		266	253	239	224	203	178	178~266	2365x595x662	398.2	398.3
BL(T)32-15	30	40		274	260	246	231	210	185	185~274	2365x595x662	398.2	398.3

Model	Power		Q (m ³ /h)	Head Range (m)							Packing Dim. (L×W×H) mm	G.W.(kg)	
	kW	HP		25	30	35	40	45	50	1665x515x562 <th rowspan="2">236.9 <th rowspan="2">244.3 </th></th>		236.9 <th rowspan="2">244.3 </th>	244.3
BL(T)45-2-2	5.5	7.5	H (m)	40	38	36	33	30	27		27~40		
BL(T)45-2	7.5	10		48	46	44	42	39	35	35~48	1245x465x532	137	144.7
BL(T)45-3-2	11	15		63	61	58	54	50	44	44~63	1665x515x562	222.5	229.9
BL(T)45-3	11	15		71	69	66	63	58	53	53~71	1665x515x562	222.5	229.9
BL(T)45-4-2	15	20		87	84	80	75	69	62	62~87	1665x515x562	236.9	244.3
BL(T)45-4	15	20		95	92	88	84	78	71	71~95	1665x515x562	236.9	244.3
BL(T)45-5-2	18.5	25		111	107	102	96	88	80	80~111	1665x515x562	258.4	265.7
BL(T)45-5	18.5	25		119	115	110	105	97	88	88~119	1665x515x562	258.4	265.7
BL(T)45-6-2	22	30		135	130	124	117	108	97	97~135	1735x545x612	306.5	313.9
BL(T)45-6	22	30		143	138	132	125	116	106	106~143	1735x545x612	306.5	313.9
BL(T)45-7-2	30	40		158	152	146	138	127	115	115~158	2165x595x662	395.2	402.5
BL(T)45-7	30	40		166	161	154	146	135	124	124~166	2165x595x662	395.2	402.5
BL(T)45-8-2	30	40		182	175	168	159	146	133	133~182	2165x595x662	397.9	405.3
BL(T)45-8	30	40		190	184	176	167	159	141	141~190	2165x595x662	397.9	405.3
BL(T)45-9-2	30	40		205	198	190	180	166	150	150~205	2165x595x662	424.3	431.7
BL(T)45-9	37	50		214	207	198	188	174	159	159~214	2165x595x662	402	409.7
BL(T)45-10-2	37	50		230	221	212	200	185	168	168~230	2165x595x662	435.8	443.1
BL(T)45-10	37	50		238	230	220	209	193	177	177~238	2165x595x662	435.8	443.1
BL(T)45-11-2	45	60		255	246	236	223	206	188	188~255	2365x645x712	500.7	508.1
BL(T)45-11	45	60		263	255	244	232	214	196	196~263	2365x645x712	500.7	508.1
BL(T)45-12-2	45	60	280	270	259	245	226	206	206~280	2365x645x712	505.1	512.5	
BL(T)45-12	45	60	289	280	268	255	236	216	216~289	2365x645x712	505.1	512.5	
BL(T)45-13-2	45	60	305	294	282	267	247	225	225~305	2425x645x712	509	517	