

CABLE PREENSAMBLADO 0,6/1KV

RESA



SECCIÓN NOMINAL	FORMACIÓN DEL CABLE CONDUCTOR		ESPESOR AISLACIÓN	DIÁMETRO EXTERNO	CARGA DE RUPTURA	RESISTENCIA ELÉCTRICA MÁX. CC A 20°C		PESO NOMINAL	CAPACIDAD DE CONDUCCIÓN DE CORRIENTE ⁽²⁾	CAÍDA DE TENSIÓN ⁽³⁾
	FASE	NEUTRO				FASE	NEUTRO			
mm ²	Nxφ		mm	mm	kgf	Ω/km	kg/km	A	V/(A.km)	
2x10	7x1,34	7x1,34	1,2	12,5	200	3,08	3,08	93	46	6,01
2x16	7x1,68	7x1,68	1,2	14,5	307	1,91	1,91	133	86	4,00
2x25	7x2,12	7x2,12	1,4	17,6	456	1,20	1,20	205	115	2,55
2x35	7x2,50	7x2,50	1,6	21,0	627	0,868	0,868	282	142	1,87
4x10	7x1,34	7x1,34	1,2	16,9	200	3,08	3,08	186	29	5,21
4x16	7x1,68	7x1,68	1,2	19,6	307	1,91	1,91	266	59	3,47
4x25	7x2,12	7x2,12	1,4	23,8	456	1,20	1,20	385	80	2,22
3x35+1x50	7x2,50	7x3,00	1,6	30,1	1605	0,868	0,676	621	100	1,63
3x50+1x50	19x1,77	7x3,00	1,6	32,7	1605	0,641	0,676	776	122	1,22
3x70+1x50	19x2,12	7x3,00	1,8	35,5	1605	0,443	0,676	958	157	0,87
3x95+1x50	19x2,50	7x3,00	2,0	39,8	1605	0,320	0,676	1244	196	0,65